

SHREE JAGANNATH SANSKRIT UNIVERSITY
SHREE VIHAR, PURI



Dev-111/2016 Letter No. 2539/2024/SJSU/Puri

dtd. 30/9/24

Corrigendum

Please refer to this office letter No. 2515/2024/SJSU,Puri, dtd. 27.09.2024 at Annexure-III in List of Electronic Material at Sl no. 1,2,4,14 has been slightly modified as per the requirement and other context will remain unchanged.


Development Officer

Memo No. 2540/2024/SJSU/Puri

dtd. 30/9/24

Copy forwarded to D.I.O, NIC,Puri with a request to upload the same in our website


Development Officer

Memo No. 2541/2024/SJSU/Puri

dtd. 30/9/24

Copy to Sri Sushanta Kumar Satapathy, Computer Instructor for information and necessary action. He is requested to display the Corrigendum in our website i.e. <http://sjsu.nic.in>


Development Officer

Annexure-III

LIST OF ELECTRONIC MATERIAL

SL NO	NAME OF THE ITEM	SPECIFICATION	QUANTIT Y
1	DIGITAL PODIUM	Digital Electronic Podium with Built-in speaker & Amplifier, Goose-neck, Cord-less and Wireless mics, Integrated Control Panel for Audio-in-and Audio-out Adjustment, Electronic panel with FM Radio, USB3.0, AUX & Bluetooth Connectivity	5
2	LAPTOP	i5, 13th Gen Intel® Core i5-1334U, 15.6-inch(39.6 cm), FHD, 8GB DDR4(3200 MHZ),512GB SSD,MSO,DualSpeakers,Win 11, Natural Silver, 1.6kg, 15-fd0220TU	31
3	DESKTOP	12th Generation Intel® Core™ i5 processor Windows 11 Home 60.5 cm (23.8) diagonal, FHD anti-glare display with Intel UMA Graphics, 8 GB DDR4 RAM 512 GB SSD Solid State Drive Keyboard and mouse combo, Wide Vision 1080p FHD IR privacy camera, 1 HDMI-out 1.4	12
4	MFM XEROX MACHINE	Multifunction Machines Mfm ,Xerox Machine (Large), Model-iR-ADV DX C5850i With Image Reader	03
5	PRINTER	Laser Output: Monochrome USB USB Print Speed Mono A4: 20 ppm Supported OS: Windows, macOS, Linux 1200X1200 dpi	14
6	AC WITH STABILIZER	Energy Efficiency- 3 Star Capacity-1.5 ton Installation Type-Splitsystem 5KVA Stabilizer	31
7	AC WITH STABILIZER	Energy Efficiency- 3 Star Capacity-2 ton Installation Type-Splitsystem 5KVA Stabilizer	6
8	WIRELESS SPEAKER MICROPHONE	AHUJA/JBL/STUDIOMASTER	23
9	CENTRAL	350 Watts Mixer Amplifier with Seven Unbalanced	12

	AMPLIFIER	Independent Mic inputs and Two Independent Auxiliary inputs	
	AUDIO AMPLIFIER	AC – 220-240V 50/60Hz, DC – 24V (2x12V Car Battery). AC – 460VA, DC – 6A. 300W Max., 250W RMS at 10% THD, 220W Max., 160W RMS at 10% THD 220W RMS at 5% THD, 200W RMS at 2% THD	12
11	AUDIO CONFERENCE CHAIRMAN UNIT MICROPHONE	63dBV/ μ bar (7.5mV/Pa) Priority Switch, Talk Switch, Speaker Volume Control, Headphone Volume, ControlMax Input 300mW	12
12	WALL MOUNTED RACK	Rack Standard : Conforms to DIN 41494 or equivalent standard Front Door : Lockable Toughened Glass Door Equipment Mounting : DIN Standard Slots Standard Finish : Powder Coated Construction : Welded Basic Frame : Steel Mounting Angle : 19" Mounting angles made of formed steel Top and Bottom Cover : Welded to Frame, Vented and Field Cable entry exit cut outs	12
13	SPEAKER	High fidelity 2-Way speaker system in compact & attractive Black or White plastic housing. The suffix B & BT denote Black cabinet, and W & WT denote White cabinet. Speaker Maximum Output Power-30 Watt Mounting Type- Wall Mount	48
14	DIGITAL PANEL	Please refer at Annexure-iv	11
15	TV	4K image resolution (3840 x 2160 pixels) 4K HDR Processor X1 Brightness (cd/m ²) Typical : 440 Contrast Ratio 1200:1 Response Time (ms) (*1) 10 Dynamic Contrast Ratio 300,000:1 Panel Type (IPS / VA) IPS Panel Surface Anti Glare Haze(%) 1 HDR Compatibility HDR10 / HLG / Dolby Vision VESA® Hole Pitch (mm) 300 x 300 Display Only (WxHxD) (mm) 1243x718x71 Display with Stand (WxHxD) (mm) 1243x787x338 Display Only (kg) 15.7 Display with Stand (kg) 16.6 Package Carton (kg) 23 Rated Power consumption (W) 196 On-Mode Power Consumption (Lot 5) (W) 97W Power Consumption (in Standby) (W) 0.5 Dimming Type Local Dimming Viewing Angle (Right/Left) 178 (89/89) degree Viewing Angle (Up/Down) 178 (89/89) degree Panel Refresh Rate (Native Hertz) 50Hz Operating System Android 10 Wi-Fi direct Yes Wi-Fi Certified Yes Wi-Fi Standard	5

		a/b/g/n/ac Wi-Fi Frequency 2.4 GHz/5 GHz (for Wi-Fi Direct: 2.4 GHz Only) Apple AirPlay (Internet required) Yes Chromecast built-in Yes Wireless LAN Integrated IP Control Yes RS-232C Control 1 (Side) Composite Video Input(s) 1 (Side) HDMI Inputs Total 4 (Side) Digital Audio Output(s) 1 (Side) Headphone Output(s) 1 (Side) USB Ports 2 (Side) Ethernet Inputs 1 (Side) RS-232C Input(s) 1 (Side)	
16	FIRE EXTINGUISHER	TIP- HD10, MEDIA weight-4.5 KG, Bruton weight-14.2 KG, TALL-590mm, DIAMETER-184mm, Working Pressure-18 bar, Pressure testing-27 bar, Length of radiant-20sec, Transmit distance-4 to 10m, Plunging gas- N2 (NITROGEN)	32
17	WATER COOLER CUM PURIFIER	Water cooler cum filter inbuilt RO with minimum Storage-50ltr (AQUA FRESH/KENT/ BLUE STAR/ DOCTOR AQUA FRESH	11

Chh
20/11/14
Coordinator, RUSA

Annexure -IV**Specification for LED PANEL**

Parameters	Specification
Panel Size	75"
Type/Tech	LED
Display Area(mm)	1650 X 928 mm
Aspect Ratio	16:9
Resolution	3840 x 2160 (4K)
Colors	1.07B Colors
Brightness	450 cd/m2
Contrast Ratio	15000:1
Response Time	4 ms
Viewing Angles	178 typ.
Backlight	LED
Backlight Life	>50000 hours
Hardness (Touch Surface)	>8H
Touch Resolution	3840 x 2160
Touch Point	40 Points(Max)
Glass Surface Technology	Anti Glare+Anti Finger Print+Antimicrobial Tempered Glass
Touch Solution	IR
Touch Screen Writing tool	Stylus or Finger
Speaker	20W x 2
Power Consumption (Standby Mode)	<0.5W
Artificial Intelligence	OEM White Board with AI Tool Kit
SoC Chipset	Amlogic 311D2
CPU	A73*4 + A53*4 (4 Core +4 Core)
GPU	G52*8 (8 Core)
RAM	8GBInBuilt
Flash Memory	64 GB InBuilt (Expandable upto 320 GB)
Android Version	13
Features	Google EDLA Supported and DN Cast
SDM/VGA	1
Display Port	1
Audio Line Out	1
RS232	1
OPS Slot	1
HDMI IN 2.0	3
HDMI OUT	1
Audio Line out	1
Microphone In	1
SPDIF	1
RJ45 (Gigabit)	In *1 & Out *1
USB 3.0 Type A	Front : 2 Rear : 2
USB 3.0 Type A to Android	1
USB Type B (Touch)	4
USB Type C	2
USB 3.0 Type C	1
WiFi Module Slot	1
OPS	Intel I5 (12 th Generation) RAM- 8 GB SSD- 1 TB
Warranty	3 Years Onsite

Chhavi
Coordinator, RUSA

